

# Firmware Update Guide



Visit support.swellpro.com for the latest version of this manual and firmware updates for your drone and accessories.

## **Flight Control Firmware Updates**

### 1. Download.

Go to <u>support.swellpro.com</u>, download the firmware.

### 2. Connect.

Turn over the aircraft, take off the "USB/Pairing Button" cover using the hex screwdriver.



Connect the aircraft and the laptop using the USB cable. Power on the aircraft. It's normal if the aircraft start to beep. Keep following the steps. The sound will go off after update is finished.



### 3. Update.

Click "Update", the flight control will start to update. Please do not disconnect the USB cable during updates.



When the bar shows 100% and changes from gray to white, the update process is complete. Disconnect the USB cable and restart the aircraft. You can reconnect the USB cable and click "Firmware Information" to check if the firmware version is up-to-date.

After finish the updates, install the cover back to the aircraft. **Ensure the orange rubber** ring is attached to the cover before installing.



### **Remote Control Firmware Updates**

### 1. Download.

Go to <u>support.swellpro.com</u>, download the firmware.

### 2. Connect.

Open the back waterproof cover, connect the remote controller to the laptop using the USB cable.



Long press the power button and remain pressing until the update is complete.



#### 3. Update.

Click "Update", the remote control will start to update. Please do not disconnect the USB cable during updates. When the bar shows 100% and changes from gray to white, the update process is complete. Release the power button. Disconnect the USB cable and

restart the remote controller. You can reconnect the USB cable and click "Firmware Information" to check if the firmware version is up-to-date.

C:\Users\ASUS\Downlo	ads\SplashDrone Remotr Control Firmwa	re\FW_Radio_SD4_0	1.25.1141.0.sfw 💿	2					~	
Click select firmware file for device 1					ENTERPRISE CONTACT US				STORE Q	
Click select firmware fil	e for device 0			0	Faare	Video D	ioupload FA	o Charle		
FW Information	USB	✓ Stop	Updati		specs	VIGEO L			OW	
irmware inform	nation			2.et	-	1		-		
					u x				2	
					~ 0	5 4	○ 搜索*Splash	Drone Remotr Con	trol Firmwa	
				mwareToolV2*			1			
				大小		<b></b> 牧日期	类型	大小		
	firmware	2021/6/18 12:51	文件本			21/8/20 11:48	SFW 文件	116 KB		
OneDrive	ScControl.dll	2020/7/16 23:15	应用程序扩展	148 KB						
一 此由該	SharkFirmwareV2	2021/5/31 17:59	应用程序	201 KB						
- 20-004	SharkToolsLbrary1.dll	2021/4/28 17:08	应用程序扩展	124 KB						
→ 网络	System.Windows.Controls.Input.Tool.	. 2020/7/16 23:15	应用程序扩展	107 KB						
	System.Windows.Controls.Layout.Too	2020/7/16 23:15	应用程序扩展	93 KB						
	WaveCtr.dll	2020/7/16 23:15	应用程序扩展	148 KB						
	WPFToolkit.dll	2020/7/16 23:15	应用程序扩展	457 KB						
									line li	

After finish the updates, press the waterproof sealing back to the remote controller.

## **Gimbal Firmware Updates**

### 1. Download.

Go to <u>support.swellpro.com</u>, download the firmware.

#### 2. Connect.

Unscrew and take off the metal cover at the back of the gimbal using the hex screwdriver.



Connect the gimbal to the laptop using the USB cable. Power on the aircraft.



### 3. Update.

Click "Update", the gimbal will start to update. Please do not disconnect the USB cable during updates. When the bar shows 100% and changes from gray to white, the update process is complete. Repeat the process for the second and the third line, after completing all three of the updates. Disconnect the USB cable and restart the aircraft.

📕 I 🖸 📕 🖬 🖬	管理 FirmwareToolV2		– 🗆 🛛		0 - 0	9 ×
文件 主页	共享 查看 应用程序工具		~ 📀		■ ☆	<b>a</b> :
$\leftrightarrow \rightarrow \star \uparrow$	GC3-S Gimbal Firmware → FirmwareToolV2	✓ Ů > 搜索*FirmwareToolV2*				-
★ 快速访问	Shark Firmware Tool 1.0			LONTACT US	STORE	_
OneDrive	C:\Users\ASUS\Downloads\GC3-S Gimbal Firmware\Firm	wareToolV2\firmware\FW_SD5_GC3_	2_01.: • 2	Video Dowr	nload FAQ Shop Now	
一 此电脑	C:\Users\ASUS\Downloads\GC3-S Gimbal Firmware\Firm	wareTooIV2\firmware\FW_SD5_GC3_	_01.' () 1			
🥏 网络	C:\Users\ASUS\Downloads\GC3-S Gimbal Firmware\Firm	0_01.: 0		- 0	×	
	FW Information	Stop	late		0 H01201+T-26-	
	Firmware information			修改日期	※ (建築 ) SSI	
9 个项目 选中	1 个项目 286 KB			2021/9/20 21:07 2021/9/20 21:07	360压缩 ZIP 文件 3,887 KB 文件夹	
S	uellPro				0 85	1
GC3-S Gim	bal Firzip ^ 2	个项目 适中 1 个项目 3.79 MB			<b>设备已准备就绪</b> "SHARKXFC"已设置并准备就绪。 一	
4 🔒				27℃ 空气优 21	へ □ 億 40 英 囲 21:23 厘	<b>P</b> 2

After finish the updates, install the metal cover back to the gimbal. **Ensure the orange rubber ring is attached to the cover before installing.** 



### **Camera Firmware Updates**

### 1. Download.

Go to <u>support.swellpro.com</u>, download the firmware. **GC1-S and GC3-S share the same camera firmware**.

### 2. Transfer.

Unzip the file and transfer it to the microSD card using an SD card reader. (The camera firmware is in BRN format.) **Ensure the BRN file is in the root directory of your microSD card, meaning on the first place when you open the microSD card, not inside the other folders.** 

 $\triangle$  Do not change the file name as it wouldn't be recognized by the camera for the update.

### 3. Update.

• Insert the microSD card into the camera. Ensure the SplashDrone 4 is powered off before you insert the microSD card.

Power on the SplashDrone 4. The camera is going to update the firmware automatically. Red & green lights flash together, indicating the camera is updating. The whole process takes about 2-3 mins. After the update is finished, the LED light will turn solid green indicating the update is finished. The firmware file will be deleted automatically.
A Do not power off the SplashDrone 4 during updates.

If you have problem update the firmware, please contact us: support@swellpro.com